

BEAR 650

SPECIFIKACIJA



MOTOR & PRENOS

Tip motora	Redni Twin četvorotaktni, SOHC, Vazdušno hladjenje
Kubikaža	648cc
Kompresija po cilindru	9.5:1
Maksimalna snaga	47.4 PS (34.9 kW) @ 7150 rpm
Maksimalni obrtni moment	56.5 Nm @ 5150 rpm
Broj obrtaja u leri	1200 ± 100 rpm
Paljenje	Digitalno paljenje varnicom
Podmazivanje	Mokar karter sa uljnom pumpom
Ulje motora	10W-50 to API SL (or higher) JASO MA2, (Fully synthetic)
Kvačilo	Mokro kvačilo, multiplate
Menjač	Šestostepeni
Co2 Emisija	99.0 g/km
Potrošnja goriva	4.16L/100Km
Emisija buke	86 dB(A)@3575rpm

DIMENZIJE & TEŽINA

Razmak osovina	1460 mm
Visina od tla	184 mm
Ukupna dužina	2216 mm
Ukupna širina	855 mm
Ukupna visina	1160 mm
Visina sedišta	830 mm
Ukupna težina sa opremom	400 kg
Kerb težina sa 90% goriva i ulja	214 kg
Kapacitet rezervoara	13.7 L

KOČNICE & GUME

Sistem kočnica	Dual Channel ABS, Switchable
Prednja	320 mm disc, ABS
Zadnja	270 mm disc, ABS
Prednji točak (Spoked Wheel)	100/90-19 M/C 57H MRF NYLOREX-F
Zadnji točak (Spoked Wheel)	140/80R17 M/C 69H MRF NYLOREX-X

ŠASIJA I VEŠANJE

Ram	Čelična dvostruka cev
Prednje vešanje	Invertovana (Upside Down) vila, hod 43 mm
Hod prednje viljuške	130 mm
Zadnje vešanje	Twin Shock
Hod zadnjeg vešanja	115 mm

ELEKTRONIKA

Sistem	12V DC
Akumulator	12 V, 12 Ah VRLA
Far	LED
Poziciono svetlo i svetlo kočnice	LED
Osvetljenje tablice	LED
Žmigavci	LED - Prdenji & Zadnji
Instrument tabla	4" okrugli TFT displej sa povezivanjem telefona, Navigacija (powered by Google Maps), kontrola medije
Punjač	USB 2.0 Type C 5 V 2 A output

BOJE



Petrol Green



Golden Shadow



Two Four Nine

