



### STEEL

An iconic silhouette, a steadfast chassis and an unwavering heart. In the last ninety years, the Bullet 350 has established itself as a resolute ally for the bravest of the brave. From the unforgiving battlefields of the 20th century to the most treacherous terrain of the Himalayas, it has proven its resilience over and over, becoming a symbol of strength and fortitude.













# ALL-NEW SEAT

The reimagined signature single bench seat has more space and improved under-thigh support, ensuring complete comfort on both quick trips and long journeys.






## LINEAGE

A short history of the world's oldest motorcycle in continuous production.


#### **1932**

GS 350cc Bullet



#### **1935**

LO 500cc Bullet



#### **1948**

Prototype 350cc Trials Bullet




#### 1949

G2 350cc Bullet



#### **1956**

JS Bullet 500cc



#### **1960**

Bullet 500cc Fury



#### **1989**

500cc Bullet



#### **1990**

350 Bullet Machismo



#### 1994

Bullet Standard 350cc





Bullet Electra 350cc

#### 2005

Bullet Electra X 500cc

#### 2008

500 Bullet Electra

#### **2013**

500 Bullet

#### 2019

Bullet Trials 500

#### 2019

Bullet X 350

#### 2020

Bullet 350

#### **2023**

The new Bullet 350













## COLOURS



**BLACK GOLD** 



STANDARD BLACK



**STANDARD MAROON** 

### SPECIFICATIONS

#### **ENGINE**

TYPE SINGLE CYLINDER, 4 STROKE, AIR-OIL COOLED

DISPLACEMENT 349CC

BORE X STROKE 72 MM X 85.8 MM

COMPRESSION RATIO 9.5:1

MAXIMUM POWER 20.2 BHP @ 6100 RPM (14.87 KW)

MAXIMUM TORQUE 27 NM @ 4000 RPM

IDLE RPM 1050+/-100

IGNITION SYSTEM ELECTRONIC FUEL INJECTION (EFI)

CLUTCH WET, MULTI-PLATE

GEARBOX 5 SPEED CONSTANT MESH

LUBRICATION WET SUMP, FORCED LUBRICATION

ENGINE OIL SAE 15 W 50 API, SL GRADE, JASO MA 2 SEMI

**SYNTHETIC** 

FUEL SUPPLY ELECTRONIC FUEL INJECTION

FUEL TYPE PETROL, UP TO E20
AIR CLEANER PAPER ELEMENT

ENGINE START ELECTRIC

SPARK PLUG BOSCH: YR7MES / CHAMPION: RER6YCA

SPARK PLUG GAP 0.7 MM TO 0.8 MM

CLUTCH WET MULTI PLATE

PRIMARY DRIVE GEAR
PRIMARY RATIO 2.313:1

GEAR BOX CONSTANT MESH

GEAR RATIO 1ST 2.615 :1

2ND 1.706:1 3RD 1.300:1 4TH 1.040:1 5TH 0.875:1

SECONDARY DRIVE CHAIN
SECONDARY RATIO 2.800:1
DRIVE CHAIN LINKS 104

#### **CHASSIS & SUSPENSION**

TYPE TWIN DOWNTUBE SPINE FRAME

FRONT SUSPENSION TELESCOPIC, 41MM FORKS, 130MM TRAVEL REAR SUSPENSION TWIN TUBE EMULSION SHOCK ABSORBERS

WITH 6-STEP ADJUSTABLE PRELOAD

### SPECIFICATIONS

#### **DIMENSIONS**

WHEELBASE 1390 MM

GROUND CLEARANCE 170 MM

LENGTH 2110 MM

WIDTH 785 MM (WITHOUT MIRRORS)

HEIGHT 1125 MM (WITHOUT MIRRORS)

SEAT HEIGHT \* 805 MM

KERB WEIGHT 195KG

GROSS VEHICLE WEIGHT 375KG

FUEL CAPACITY 13 LTR

#### **BRAKES & TYRES**

WHEEL RIM FR. 2.15 X 19

WHEEL RIM RR. 3.0 X 18

TYRES FR. SPOKES WHEEL - 100/90 - 19" - 57P (TUBE TYPE)

TYRES RR. SPOKES WHEEL - 120/80 - 18" - 62P (TUBE TYPE)

TYRE PRESSURE

FRONT SOLO - 32 PSI, WITH PILLION - 32 PSI

REAR SOLO - 32 PSI, WITH PILLION - 36 PSI

BRAKES FRONT 300 MM DISC WITH TWIN PISTON FLOATING

**CALIPER** 

BRAKES REAR 270 MM DISC, SINGLE PISTON FLOATING

**CALIPER** 

ABS DUAL CHANNEL

#### **ELECTRICALS**

ELECTRICAL SYSTEM 12 VOLT - DC

BATTERY 12 VOLT, 8 AH, VRLA (MAINTENANCE FREE)


HEAD LAMP 12V, H4-60/55W (HALOGEN)

TAIL LAMP 12V, P21/5W

TURN SIGNAL LAMP 12V, 10W X 2 NOS

# GENUINE MOTORCYCLE ACCESSORIES

#### **ENGINE GUARD**



BLACK AIRFLY ENGINE GUARD



SILVER AIRFLY ENGINE GUARD

#### **SUMPGUARD**



SILVER SUMPGUARD

#### **BODYWORK**



BLACK AEROVISOR

#### **SEATS**



BLACK TOURING DUAL SEAT



BROWN LOW RIDE DUAL SEAT



BLACK PASSENGER BACKREST PAD

#### **CONTROLS**



SILVER DELUXE FOOTPEGS



BLACK TOURING MIRRORS

#### LUGGAGE



BLACK COMMUTER PANNIER

